

DR Duplex Receptacle

DESCRIPTIONS

Packaged in a touch-proof enclosure to eliminate the possibility of accidental shock. The universal mounting foot allows the outlet box to be mounted either vertically or horizontally in your panel. Touch-proof screw terminal block provides a reliable connection.

FEATURES

- DIN-rail mount duplex receptacle
- Vertical or horizontal mounting
- Snap on foot provides fast installation or can be fixed with screws in control cabinet
- Fits on 35 mm wide DIN-rail
- Ground prong reversed for greater protection
- Screw terminal connection via touch-proof terminal blocks
- Available with GFI (Ground Fault Interrupting)
- UR Recognized

APPLICATIONS

- Test & Diagnostic Equipment
- Computers/Printers
- Power Tools
- Soldering Iron
- Displays
- Lighting
- Fan



GENERAL SPECIFICATIONS

Technical Data

Rated Voltage	120 V AC
Rated Current	.15 or 20 AMPS
Maximum Wire Size	#10 AWG

Housing Data

Color	Black
Material	PVC V01550
Maximum Temperature	40° C

Dimensions

Length	.532 in. (135 mm)
Width	.295 in. (75 mm)
Depth	.256 in. (65 mm)

DR Duplex Receptacle Selection Chart

AMP	CATALOG NUMBER	APPROX. SHIP WEIGHT LBS (Kg)
15	DRR-15	.41 (.19)
15	DRR-15GFI	.46 (.21)
20	DRR-20	.41 (.19)
20	DRR-20GFI	.46 (.21)

Redundancy Applications

For critical load applications redundancy may be required

All the DR Series power supplies can be connected in parallel for redundancy, so if one power supply fails, there is adequate power reserve in the remaining unit to continue supporting the critical load (Reference Figure 1).

