



Search [GO](#) Search Options

visit our other sites: [FTZ](#) | [Utilco](#) | [IlSCO Canada](#)

[My IlSCO](#) | [Home](#) | [About Us](#) | [Products](#) | [Reference](#) | [Customer Service](#) | [Contact Us](#) | [Distributors](#) | [Price & Availability/Order](#)

SPAR SPLICER/REDUCER INS.

- ClearSplice(TM) has transparent flexible insulating cover to insulate yet allow visual inspection.
- Captive pressure screws in 'Quick-start' position.
- Range adjustable trim-to-fit for proper fit to cable.
- Unique 'Rocket' design.
- UL Listed and CSA Certified for 600 Volts.
- Dual Rated for Copper and Aluminum Conductor.



Narrow Criteria by Wire Range [GO](#) [Show All](#)

* Catalog Numbers link to CAD files (if available)

Catalog No.	Wire Range	Length	Width	Height	Hex Size	N.A.E.D. No.
SPAR-2	2-14 STR.	3.83	1.75	.95	S	78366985722
SPAR-4	4-14 STR.	3.3	1.55	.76	S	78366985720
SPAR-1/0	1/0-14 STR.	4.8	1.94	1.14	S	78366985724
SPAR-4/0	4/0-6 STR.	5.67	2.43	1.5	5/16	78366985726
SPAR-250	250 MCM-6 STR.	7.91	2.43	1.62	5/16	78366985728
SPAR-350	350 MCM-6 STR.	7.91	2.43	1.62	5/16	78366985730
SPAR-500	500 MCM-3/0 STR.	8.86	3.23	2.04	3/8	78366985732

[RETURN](#)